AQUASPORTS MARINE

BOATING

AQUASPORTS

Marine

SUPER CENTRE

Mercury 0.00

0

Phone: 08 9250 3339

Email: info@aquasportsmarine.com.au

Website:

Boat Details

Price POA Boat Brand
Model 250 HP Length

Year 2021 Category Boat Engines and Outboards

Hull Type

Hull Style
Power Type

Stock Number

Condition New State Western Australia

Suburb MIDVALE Engine Make

Description

The new Mercury 250hp FourStroke is precision engineered from skeg to cowl. Packed with advanced technology to improve all aspects of performance and reliability. the Robust 4.6 Litre V-8 engine is designed to minimise weight and maximise fuel economy. Delivering Mercury's best ever FourStroke hole shot, top speed and fuel efficiency. The 250hp FourStroke now comes with a 3+3=6 Year factory warranty.ENGINE DETAILS

Quick-revving double-overhead camshaft design and deep-breathing intake deliver thrilling and satisfying performance. Great for aluminum console, deck, inflatable rigid hull, inshore fishing, offshore fishing, and runabout boats and tritoons. SPECIFICATIONS - 250 HP / kW

• 250 / 186

Engine type

• V-8

MidSection

Conventional MidSection

Displacement (CID/CC)

• 279 CID

Displacement (L)

• 4.6L

Cylinder Configuration

• V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM

• 5200-6000

Air induction

• Performance-Tuned Long-Runner Intake Manifold

Fuel induction system

• Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt

• 85-amp (1071 Watt) with Idle Charge

Recommended fuel

• Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

• NMMA Certified FCW SAE 10W-30

Engine protection operator warning system

• SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

• Yes

Starting

• Electric Start with SmartStart Protection

Controls

• Remote Mechanical or Digital Throttle & Shift (DTS)

Steering

- Big Tiller (optional)
- Hydraulic (standard)
- Power (optional)

Shaft length • 20" / 508 mm • 25" / 635 mm • 30" / 762 mm Gearcase ratio • 1.75:1 Dry weight *Lightest model available • 527 lbs / 239 kgs CARB star rating • 3

Bore and stroke

• 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

• SmartCraft PCM 112 Digital Inductive

Cooling system

• Water-cooled with thermostat

Gear shift

• F-N-R

Gearcase options

• 5.44"

Trim system

Power trim and tilt

Exhaust system

• Through prop

Counter Rotation

• Available

Color

- Cold Fusion White
- Pearl Fusion White
- Phantom Black
- Warm Fusion White

Lubrication system

• Integrated wet sump

Oil Capacity

• 7.0 Quarts / 6.6 Liters

Maximum Trim Range

• 20° (-6° to 14°)

Maximum Tilt Range

• 73° (-6° to 67°)

Engine Details

Displacement Horse Power Steering Fuel Capacity 4.6 250

Big Tiller (optional), Hydraulic (standard), Power (optional)

6.6