



250R

POA

Specifications

Boat Details

Price	POA	Boat Brand	Mercury
Model	250R	Length	0.00
Year	2021	Category	Boat Engines and Outboards
Hull Style		Hull Type	
Power Type		Stock Number	0
Condition	New	State	Western Australia
Suburb	MIDVALE	Engine Make	Mercury

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: 08 9250 3339

Email: info@aquasportsmarine.com.au

Website:

189 Bannister Road Canning Vale WA 6155

Description

The 250R FourStroke pumps out 250 propshaft horsepower. The stout V-8 powerhead provides an astounding 53% increased displacement and up to 40% higher overall bottom-end torque than the legacy two-stroke 250XS it replaces. Transient spark calibration boosts torque by 7% for unmatched acceleration. Advanced Range Optimisation (ARO) automatically adjusts fuel delivery for up to 10% improvement in cruise-speed fuel efficiency. All of this on regular 91-RON Unleaded fuel, while maintaining a comparable weight to the 250 XS. Specifications

- RATED HORSEPOWER (HP/KW) 250/186
- BORE & STROKE (IN/MM) 3.6 x 3.4/92 x 86
- IDLE RPM 600
- MAX RPM AT FULL THROTTLE 5800-6200
- CYLINDERS/ENGINE CONFIGURATION V-8 (64 degree) with 32-valve Dual Overhead Cam (DOHC)
- DISPLACEMENT (LITER/CID) 4.6/279
- INDUCTION SYSTEM Performance-Tuned Long Runner Intake Manifold
- FUEL SYSTEM Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
- FUEL REQUIREMENTS Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON
- IGNITION SYSTEM SmartCraft PCM 112 Digital Inductive
- CHARGING SYSTEM 85-amp (1071 Watt)
- STARTING Electric Start with SmartStart Protection
- LUBRICATION SYSTEM Integrated wet sump
- OIL REQUIREMENT NMMA Certified FCW SAE 10W-30
- THROTTLE AND SHIFT CONTROLS Mechanical
- MIDSECTION DESIGN Tri-Ram Midsection with High-Durometer Elastomer Upper Mount and Solid Lower Mounts
- SHAFT LENGTH (IN./MM.) 20/508
- GEARCASE Sport Master
- GEAR RATIO 1.75:1
- WEIGHT (LBS./KGS.) 520/236
- WARRANTY 3-Year Limited

Engine Details

Engine Make

Mercury

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.