



Phone: 08 9250 3339
Email: info@aquasportsmarine.com.au
Website:

Boat Details

Price	POA	Boat Brand	Mercury
Model	115 HP Sea Pro Fourstroke	Length	0.00
Year	2021	Category	Boat Engines and Outboards
Hull Style		Hull Type	
Power Type		Stock Number	0
Condition	New	State	Western Australia
Suburb	MIDVALE	Engine Make	

Description

Mercury Seapro 115HP Fourstroke - These commercial outboards are designed to work as hard as you do...engineered to be ultra tough working partners for anyone making their living on the water. Every SeaPro features unique components to cope with the additional demands of professional operation. Whatever your job there's a specific FourStroke of TwoStroke Mercury SeaPro model that's up to the task.

HP / kW

- 115 / 86

Engine type

- 8-valve single overhead cam (SOHC)
- Inline 4

Displacement (L)

- 2.1

Full throttle RPM

- 5000-5500

Air induction

- Performance-Tuned Scroll Intake Manifold

Fuel induction system

- Computer Controlled Multi-Port Electronic Fuel Injection (EFI)

Alternator amp / Watt

- 35 amp / 441 watt with water-cooled voltage regulator

Recommended fuel

- Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

- NMMA Certified FCW 25W-40 Synthetic Blend

Engine protection operator warning system

- SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

- Yes

Starting

- Smart Start Electric

Controls

- Mechanical throttle & shift

Steering

- Big Tiller
- Dual Cable Mechanical
- Electro-Hydraulic Power Steering Optional on Duals
- Hydraulic

Shaft length

- 20" / 508 mm
- 25" / 635 mm

Gearcase ratio

- 2.38:1

Dry weight *Lightest model available

- 363 lbs / 165 kg

Bore and stroke

- 3.5 x 3.2" / 90 x 81 mm

Ignition

- SmartCraft ECM 70 Digital Inductive

Cooling system

- Water-cooled with thermostat

Gear shift

- F-N-R

Trim system

- Power Tilt
- Power Trim

Exhaust system

- Through prop

Shallow water trim range (degrees)

- 20

Counter rotation

- Available

Color

- Phantom Black

Lubrication system

- Integrated Dry Sump

Oil Capacity

- 5.5 qts / 5.2l

Maximum Trim Range

- 22° (-6° to 16°)

Maximum Tilt Range

- 70° (-6° to 64°)

Features

Horse Power (hp)	115
------------------	-----

Engine Details

Horse Power	115
-------------	-----